



TM

EMMTEK MACHINERY

An ISO 9001:2015 Certified Company

金三阳机械

Jinsanyang Machinery



Weaving Success

BETA X 喷水织机

BETA X WATER JET LOOM

BETA X

产品特点:

BETA X机型是改进创新的机型，从送经、开口、卷取、传动系统到整机稳固性都加以全面改进优化，具有高速稳定连续运转能力，对织造轻薄及中密度织物更具有良好表现，产品适应范围宽广。用户可选配本公司最新研究成功的电子送经、电子卷取系统，纬密变化及慢点动平织开口，以满足更高品质和附加值织物的生产需求。本机型可选配凸轮开口、多臂开口配置、提花装置；单泵单喷、单泵双喷、双泵双喷、双泵三喷、双泵四喷电子自由选纬系统。

Product Features

BETA X model is a professional model with improvement and innovation, machine let-off, shedding, taking-up, transmission system and whole parts are optimized and improved, It has capability for running at high speed stably, and has good performance for weaving light and medium density fabric, the products have wide range use. The optional electronic let off (ELO), electronic take up (ETU), weft density variation and speed changing device can satisfy weaving demand for higher quality and more valuable fabrics. The options can be :cam/dobby shedding; single pump single - nozzle / double-nozzle; two-pump two-nozzle/ three-nozzle / four-nozzle.

Feeder Model SHJ.M - High Speed Weft insertion

Suitable for.

- Specially designed software for high speed weaving technology
- Highly sensitive weft sensor (feeler) (adv. less stoppage)
- Dual Brake system (adv. for preventing starting mark stop mark)



For Contact : +91 98255 16163 / +91 97276 24658

BETA 型喷水织机主机配置表 Main Parts Description of BETA series

| | |
|-------------------|---|
| Reed | 150cm, 170cm, 190cm, 210cm, 230cm, 250cm, 280cm, 300cm, 320cm, 340cm, 350cm, 360cm |
| Effective Reed | 210cm-(0-50cm), 230cm-(0-70cm) 0-50cm under 210cm(standard), 0-70cm above 230cm(optional) |
| Power | 2.2-4.0kw |
| Structure | case structure, oil lubrication system |
| Nozzle | 1-4 (set) |
| Pump | 1-2 (set) |
| Measureing Feeder | (RDP) or electronic measuring & storage system |
| Beating | bicrank multilaid beating structure |
| Shedding | plain/cam/dobby |
| Heald Frame | (MAX) 8/10/16 (pic) |
| Let off | (MLO) MLO, stepless speed transmission, belt transmission mode (optional) |
| | (ELO) electronic let off (optional) |
| | 800mm, 914mm, 1000mm beam diameter : 800mm(standard), 914mm, 1000mm(optional) |
| | L/R bi-bearing, bi-cudgel (standard), style for high-density fabric (optional) |
| Take up | (MTU), 5-60/cm, 35-90/cm mechanical take up.Weft density:5-60picks/cm(standard), 35-90picks/cm(optional) |
| | (ETU) : 17-82/cm electronic take up(optional).Weft density:17-82picks/cm |
| | S or L take-up pattern, MAX.diameter : 520mm |
| Catch Cord Device | gears cross-twist system, automatic yarn cutting sensor |
| Yarn-end Disposal | false twist spindle |
| Weft Cutting | mechanical cutter |
| Electric | super optical feeler |
| | Push-Button operation panel or touching operation panel for warmup, start, stop, inch, reversed inch |
| | digital watch indicates output, speed, efficiency and stop frequency |
| | 4-color lamp for indicating stop cause |
| | slow-motion system |
| Blower | mechanical (standard), electric (0.375kw) (optional) |
| Weft Supply Stand | Landen, fixed and two-eight picks per set |

青岛金三阳纺机科技有限公司

Qingdao Jinsanyang Textile Machinery Technology Co., Ltd.

地址: 青岛市黄岛区王台镇 邮编: 266425

Add : Wangtai Town, Huangdao District, Qingdao, China.

Tel : +86 532 8313 6898 , Fax : +86 532 8313 3536

Email : info@jinsanyang.com, qingdaojsy@gmail.com

Web : www.jinsanyang.com

Shreeji International Inc.

Plot No. 125/126, Royal Ind. Estate,
Opp. Shiv Shakti Ind. Estate At Delad,
Sayam-Amroli Road, Sayam, Surat. (Guj.) India.
Email : info@emmetek.co.in, royalnet2001@gmail.com

For Contact :

+91 98255 16163 / +91 97276 24658