



# EMMTEK MACHINERY

An ISO 9001:2015 Certified Company

## CHINA'S BEST BRAND

Qingdao Jinsanyang Textile Machinery Technology Co. Ltd



Weaving Success

## MODEL NO. 410-H

## DIGITALLY SMART WATERJET LOOM SERIES

### GET DAILY REPORTS ON YOUR COMPUTER & MOBILE

#### Features

- Loom Monitoring System
- Auto Reverse System
- Slow Inching System
- Fully Computerised Machine
- Electronic Let of (Optional)
- Electronic Take of (Optional)
- Mechanical Dobby (Synchronise with Feeder System)
- Heavy Loom Body (Weight - 450kg - 40mm Thickness)
- Gear Box HT200 Material
- Back Rest Roll (Heavy Titanium Coted)
- Rocking Shaft Bracket Solid 10mm
- Tempule S.S 304
- Maintenance Free Electronic Panel



For Contact : +91 98255 16163 / +91 97276 24658

# 410-H 型喷水织机主机配置表 Main Parts Description of 410-H series

Reed	150cm, 170cm, 190cm, 210cm, 230cm, 250cm, 280cm, 300cm, 320cm, 340cm, 350cm, 360cm
Effective Reed	210cm-(0-50cm), 230cm-(0-70cm) 0-50cm under 210cm(standard), 0-70cm above 230cm(optional)
Power	2. 2-4.0kw
Structure	case structure, oil lubrication system
Nozzle	1-4 (set)
Pump	1-2 (set)
Measuring Feeder	(RDP) or electronic measuring & storage system
Beating	bicrank multilaid beating structure
Shedding	plain/cam/dobby
Heald Frame	(MAX) 8/10/16 (pic)
Let off	(MLO) MLO, stepless speed transmission, belt transmission mode (optional)
	(ELO) electronic let off (optional)
	800mm, 914mm, 1000mm beam diameter : 800mm(standard), 914mm, 1000mm(optional)
	L/R bi-bearing, bi-cudgel (standard), style for high-density fabric (optional)
Take up	(MTU), 5-60/cm, 35-90/cm mechanical take up.Weft density:5-60picks/cm(standard), 35-90picks/cm(optional)
	(ETU) : 17-82/cm electronic take up(optional).Weft density:17-82picks/cm
	S or L take-up pattern, MAX.diameter : 520mm
Catch Cord Device	gears cross-twist system, automatic yarn cutting sensor
Yarn-end Disposal	false twist spindle
Weft Cutting	mechanical cutter
Electric	super optical feeler
	Push-Button operation panel or touching operation panel for warmup, start, stop, inch, reversed inch
	digital watch indicates output, speed, efficiency and stop frequency
	4-color lamp for indicating stop cause
	slow-motion system
Blower	mechanical (standard), electric (0. 375kw) (optional)
Weft Supply Stand	Landen, fixed and two-eight picks per set

## 青岛金三阳纺机科技有限公司

**Qingdao Jinsanyang Textile Machinery Technology Co., Ltd.**

地址: 青岛市黄岛区王台镇 邮编: 266425

Add : Wangtai Town, Huangdao District, Qingdao, China.

Tel : +86 532 8313 6898 , Fax : +86 532 8313 3536

Email : info@jinsanyang.com, qingdaojsy@gmail.com

Web : www.jinsanyang.com

## Shreeji International Inc.

Plot No. 125/126, Royal Ind. Estate,  
Opp. Shiv Shakti Ind. Estate At Delad,  
Sayam-Amroli Road, Sayam, Surat. (Guj.) India.  
Email : info@emmetek.co.in, royalnet2001@gmail.com

**For Contact :**

**+91 98255 16163 / +91 97276 24658**